SUBSOIL INVESTIGATION REPORT

FOR THE CONSTRUCTION OF 5 MLD WATER
TRETAMENT PLANT AT ERATTAYAR TO PROVIDE
FHTCS TOM ALL HOUSE HOLDS TO ERATAYAR AND
KAMAKSHI G P UNDER JALAJEEVAN MISSION



GEOTECHNICAL ENGINEERING LABORATORY

CIVIL ENGINEERING DEPARTMENT

AL-AMEEN ENGINEERING COLLEGE, KULAPPULLY P.O, SHORNUR – 2, PALAKKAD

October-22



DEPARTMENT OF CIVIL ENGINEERING

SUB SOIL INVESTIGATION REPORT

Name of client

: Shri. Sajeev C. George, C5, Good Earth Haveli,

Thripunithura. Ernakulam Dist.

Site of investigation : Three bore in Erattayar Panchayaths.

Period of investigation

: 26-9-22 TO 27-9-22

Ref: No.

: AL-AM/GE/0285/22 Dated 7-10-22

Laboratory

: AL-Ameen Engineering College, Kulappully.P.O.

Analysis done by

Date: 7-10-2022

: Prof. K. Murar

Consultant

Al-Ameen Engineering College. **CHARTED ENGINEER (FIE 16619/03)**

(Retired Professor, Civil Dept.

N.S.S. College of Engineering, Palakkad.)

Prof. MURARI. K, M. Tech. CONSULTANT DEPARTMENT OF CIVIL ENGINEERING AL-AMEEN ENGINEERING COLLEGE KULAPPULLY P.O., SHORANUR - 2,

FOR THE CONSTRUCTION OF 5 MLD WATER TRETAMENT PLANT AT ERATTAYAR TO PROVIDE FHTCS TOM ALL HOUSE HOLDS TO ERATTAYAR AND KAMAKSHI G P UNDER JALAJEEVAN MISSION

Shri. Sajeev C. George, C5, Good Earth Haveli, Thripunithura. Ernakulam Dist, as per letter dated 27-9-22, requested to The Principal, AL-Ameen Engineering College, for arranging the analysis and preparation of investigation report of the Erattayar site. The Principal, AL-Ameen Engineering College authorized to take up the consultancy work by Prof. Murari.K, the consultant of the college.

INVESTIGATION


Shri. Sajeev C. George, C5, Good Earth haveli, Thripunithura, conducted the deep soil investigation at three locations for the Jalajeevan Mission Project. Shri. Sajeev C. George, C5, Good Earth Haveli, Thripunithura, supplied the soil samples and the bore logs of three bores to the Geotechnical Engineering laboratory of this institution. The soil samples are matching with the bore logs supplied.

OBSERVATION

It is proposed to construct a water treatment plant of capacity 5 MLD at this location.

In bore -1 - it is seen that the top soil is filled black soil up to a depth of 0.80 m below ground level. From 0.80 m depth there is fair quality hard rock exists. The bore log is shown in fig-2.

In bore -2 - the top soil is filled black soil up to a depth of 2.20 m below ground level. The second layer is loose lateritic soil of 1.80 m thick. The third layer is lateritic soil of 1.20 m thick. From 5.20 m depth there is soft rock of 2.65 m thick exists. Below the soft rock fair quality hard rock exists at 7.85m deep from GL. The bore log is shown in fig-3.



In bore -3 - the top soil is filled black soil up to a depth of 1.75 m below ground level. The second layer is soft rock of 2.05 m thick exists. Below the soft rock fair quality hard rock exists at 3.80 m deep from GL. The bore log is shown in fig-4.

From the bore log and the test results it is seen that the soil strata changes in the three bore locations. Hence the recommended soil parameters are shown in Table-1, II & III for the bore-1, 2 & 3 respectively. The recommended Safe Bearing Capacity (SBC) for different soil strata at different depths are also shown in the tables for here boreholes.

RECOMMENDATIONS

From the bore log and the soil properties, it is recommended to provide isolated shallow footing on the rock strata available at shallow depth at the site. In bore-1, rock is available at depth of 0.80 m and in bore -3; rock is available at depth of 1.75 m belowground level at this location. In bore-2, rock is available at depth of 5.20 m only. Hence for foundations similar to bore-2 locations end bearing short piles anchored to hard rock may be used to support the columns.

TABLE-1

Soil Properties	Bore- I
	Depth(m)
	0.80
Bulk density (g/cc)	
Cohesion (C) (kg/cm ²)	
Angle of internal Friction (φ)	
Safe Bearing Capacity of rock (SBC) (T/m ²)	755

TABLE-11

Soil Properties	BH No-II Depth(m)									
	1	2	3	4.5	5.2					
Bulk density (g/cc)	1.61	1.64	1.74	1.92						
Cohesion (C) (kg/cm ²)	0.05	0.06	0.10	0.20						
Angle of internal Friction (φ)	18	18	22	26						
Safe Bearing Capacity (SBC)(T/m ²)	5	8	12	25	40					
Safe Bearing Capacity of rock (T/m ²)										




TABLE-1II

Soil Properties	BH No-III								
		I	Depth(m)						
	1	1.75							
Bulk density (g/cc)	1.93	-							
Cohesion (C) (kg/cm ²)	0.08								
Angle of internal Friction (φ)	20								
Safe Bearing Capacity (SBC)(T/m ²)	10	40							
Safe Bearing Capacity of rock (T/m2)			720						

BORE LOCATIONS AT ERATTAYAR SITE FOR 5 MLD WTP




Fig-1

AL AMEEN ENGINEERING COLLEGE, KULAPPULLY

GEOTECHNICAL ENGINEERING LABORATORY

Type of boring: Rotary drilling

Bore loge and data sheet

Date of commence: 26-9-22

Date of completion: 26-9-22

Depth Soil Profile below			Thickness of layer	Standard Penetration test								Remarks	
G/L Of 30H	Thi	Depth in m	'N' Value	10	20	30	40	50	>50				
0.00		Filled soil (Black)	0.80										
		Hard Rock	1.00	0.80	SPT				O SA	Ц	Æ		
1.80 Boreho	le terminate	d at 1.80 m in har	rd Rock	-	L	Boring with D/C Bit					RQD=65% (Fair)		

Client

: Shri. Sajeev C. George, C5, Good Earth Haveli, Thripunithura

Project

: Investigation for 5 MLD WTP at Erattayar

Borehole number

: 1

Reduced level of bore hole at GL

Position of water table

Fig-2



AL AMEEN ENGINEERING COLLEGE, KULAPPULLY

GEOTECHNICAL ENGINEERING LABORATORY

Type of boring: Rotary drilling

Bore loge and data sheet 2/3

Date of commence: 26-9-22

Date of completion: 26-9-22

Depth Soil Profile below				Thickness of layer test test			iph o		Remarks			
G/L	Thi	Th T	N,	10	20	30	40	50	>50	V 2.		
2.20		Filled soil (Black)	2.20	1.0	3	1						
1.00		Lateritic soil Soft (Red)	1.80	3.0	7					3	1	
		Lateritic soil	1.20	4.5	15		_	/				
.20	**********			5.20	SPT	REB	OUN	D W	O SA	MPI	E	
		Soft Rock				Borin	g wit	h D/C	Bit			
7.85			2.65	7.85								
3.85		Hard Rock	1.00									RQD=67% (Fair)

Client

: Shri. Sajeev C. George, C5, Good Earth Haveli, Thripunithura

Al-Ameen Engineering

College, Kulappully

Project : Investigation for 5 MLD WTP at Erattayar

Borehole number

: 2 Reduced level of bore hole at GL : ---

Position of water table

Fig-3

AL AMEEN ENGINEERING COLLEGE, KULAPPULLY

GEOTECHNICAL ENGINEERING LABORATORY

Type of boring: Rotary drilling

Bore loge and data sheet 3/3

Date of commence: 27-9-22

Date of completion: 27-9-22

Depth Soil Profile below				Standard Penetration test		Gra	ph o		Remarks			
G/L OI SO	description of laker of laker of laker lak		Value	10	20	30	40	50	>50			
1.75		Filled soil (Black)	1.75	1.00 7								
3.80		Soft Rock	2.05	1.75		RE Borin				AMP	LE	
4.80		Hard Rock ed at 4.80 m in hard	1.00	3.80								RQD=69% (Fair)

Client

: Shri. Sajeev C. George, C5, Good Earth Haveli, Thripunithura

Project

: Investigation for 5 MLD WTP at Erattayar

Borehole number

: 3

Reduced level of bore hole at GL

Position of water table

: --



Note

The recommendations are based on soil conditions as revealed at the points indicated in the site plan, and depths to which bore holes are taken. Any change or difference observed at other points or depths during construction should be closely monitored and changes in design / construction methods should be made if necessary. Any clarifications may be made within six months from the date of this report

Yours faithfully

Al-Ameer Engineering College, Kulappully

Prof.MUARLE, M.Tech

CONSULTANT,

CHARTED ENGINEER (FIE 16619/03) (Retired Professor, Civil Dept. N.S.S. College of Engineering, Palakkad.)

7-10-2022

Prof. MURARI. K, M.Tech.
CONSULTANT
DEPARTMENT OF CIVIL ENGINEERING
AL-AMEEN ENGINEERING COLLEGE
RULAPPULLY P.O., SHORANUR - 2,