LETTER OF ACCEPTANCE

To,

Sri/Smt M/s.CIJOE.P.S PAN: ATNPC0519J

Your e-Tender No WRD/KWA-CE(CR)/TR/11852/2022_5_1_1/1 dated 23-03-2023 for the Jal Jeevan Mission (JJM)-WSS to Pavaratty & Date: Mullassery Panchayaths in Chavakkad Taluk (Phase 2) - Balance works-State Plan -Supplying, Laying, Testing and Commissioning 300/250/200mm DI K9 Gravity main from Chattukulam to Pavaratty and Mullassery OHSR including Railway push through level cross at Brahmakulam--LSGD Road Restoration Charges for 20mm Open Graded Chipping Carpet-General Civil Work has been accepted for a quoted amount of Rs. 15205000/- (Rupees One Crore Fifty Two Lakh Five Thousand only) based on rates quoted for individual itemsindividual items which is mentioned in the accompanying schedule. You are directed to submit the stamp GRN ID/Stamp paper, Performance Guarantee and Additional Performance Guarantee as mentioned below and execute an agreement and start the work within a week after getting necessary instructions from the Executive Engineer(Project Division Nattika). The time allowed for executing agreement without fine will be 14 (Fourteen) days from the date of issue of letter of acceptance and a further period of 10 (Ten)days time will be allowed to execute the agreement after realizing a fine of Rs. 25000/- (Twenty Five Thousand Only). This fine shall be remitted in favour of the Managing Director, Kerala Water Authority, Account No - STSB 701011400000181, District Treasury, Thiruvananthapuram through e-treasury payment gateway.

- 1. stamp paper required value RS. **15210/-** (**Fifteen Thousand Two Hundred and Ten Only**) shall be submitted to the Agreement Authority. (subject to govt orders)
- 2. Before executing the agreement, you should deposit a Performance Guarantee of 5% of contract value, ie. Rs. 760250/- (Rupees Seven Lakh Sixty Thousand Two Hundred and Fifty only) and should be submitted within 14 (Fourteen) days of receipt of this LOA (Letter of Acceptance) as below.
- a) At least **Fifty** (50%) of Performance Guarantee shall be in the form of Treasury Fixed Deposit in the name of Agreement Authority for a period not less than 28 (twenty eight) days after the completion of defect liability period.
- b) Balance Performance Guarantee shall be in the form of bank guarantee. Bank Guarantee is to be submitted in the format prescribed by the Employer in the bid document. Bank Guarantee shall be unconditional and it shall be from any Nationalized/ Scheduled Bank/ Kerala Financial Corporation/ District Co-operative Banks, Primary Co-operative Banks, Urban Co-operative Banks or any other forms prescribed in the revised PWD Manual to be submitted before executing agreement and shall be valid till 28 (twenty eight) days after the completion of defect liability of the Work, in approved format. The Bank Guarantee on instalment basis with lesser period of validity shall not be accepted.
- 3. An Additional Performance Guarantee of Rs. **55186/- (Rupees Fifty Five Thousand One Hundred and Eighty Six only)** shall be also deposited for unbalanced price in addition to the normal Performance Guarantee in the following form and it should be to be submitted before executing agreement.
- a) At least Fifty percent (50%) of Additional Performance Guarantee shall be in the form of Treasury Fixed Deposit in the name of Agreement Authority for a period not less than 28 (twenty eight) days after the completion of the work.
- b) Balance Additional Performance Guarantee Treasury shall be in the form of bank guarantee. Bank Guarantee is to be submitted in the format prescribed by the Employer in the bid document. Bank Guarantee shall be unconditional and it shall be from any Nationalized/ Scheduled Bank/ Kerala Financial Corporation/ District Co-operative Banks, Primary Co-operative Banks, Urban Co-operative Banks or any other forms prescribed in the revised PWD Manual and shall be valid till 28(twenty eight) days after the completion of the Work, in approved format. The Bank Guarantee on instalment basis with lesser period of validity shall not be accepted.

- a) Full amount of additional performance guarantee shall be accepted in case of guarantees issued by Kerala Financial Corporation
- 4. In addition to Performance Guarantee and Additional Performance Guarantee, Performance Security Deposit at the rate 2.5% of Bill amount will be deducted from running bills.
- 5. Solicitor's fee, if any, to be paid to the Law Officers of Government for scrutinising or drawing up of agreements-will be paid and the same recovered from the successful bidder.
- 6. You are requested to take an Insurance cover for this work for an amount of Rs. **200000** /- (**Rupees Two Lakh only**) and submit the same within 15 days of Start of work subjected to the provisions provided in the Bid Document. 0.2% of the Contract Amount will be deducted in the event of failure to submit the Insurance to the concerned Authorities as noted above. (The value shall be generally 0.5% of the Contract Value subject to a minimum of Rs. 2.00 lakh and maximum of Rs. 5.00 lakh.).
- 7. Engineering personnel in addition to other supporting staff as detailed below for tenure of the contract for works supervision shall be employed.

Works Manager- 1no (Civil Engineering Graduate with minimum 3 years experience) and Site Engineers- 2 nos (one Civil Engineering graduate and one civil diploma holder with minimum 1 year experience).

- 8. The Contractor shall enter into a Contract Agreement with the Agreement Authority within 14 Fourteenworking days from the date of 'Acceptance of Tender' or within such extended time as may be granted by the Agreement Authority. The date of despatch of Letter of Acceptance through Contractors Portal shall be the date of Acceptance of Tender.
- 9. In the eventuality of failure to produce the original documents, or submit the performance security, or enter into agreement with the Agreement Authority within the specified time limit, the Bidder shall be debarred in future from participating in all Government Bids for three years and will be recommended for blacklisting by the competent authority. In such cases, the Government may rearrange the work otherwise or get it done departmentally at the risk and the cost of the Bidder and the loss so sustained by the Government can be realized from the Bidder under the Revenue recovery Act or otherwise the Government may decide.
- 10. The work should be completed in all respects within 6 months from the date of handing over the site.
- 11. Defect Liability period will be 2 years
- 12. All the details mentioned above shall be submitted to the Agreement Authority within 14 (fourteen) days from the date of 'Acceptance of Tender' or within such extended time as may be granted by the Agreement Authority.
- 13. All the terms and conditions of the Notice Inviting tenders and tender shall be binding on the Contractor.

Bindu T B(G11373)
Superintending Engineer

ACCEPTED SCHEDULE

Name of Work: Jal Jeevan Mission (JJM)-WSS to Pavaratty & Mullassery Panchayaths in Chavakkad Taluk (Phase 2) - Balance works-State Plan -Supplying, Laying, Testing and Commissioning 300/250/200mm DI K9 Gravity main from Chattukulam to Pavaratty and Mullassery OHSR including Railway push through level cross at Brahmakulam--LSGD Road Restoration Charges for 20mm Open Graded Chipping Carpet-General Civil Work (DSR 2018 with Cost Index 135.59)

Sl No	Description of work	No. or Qty.	Unit	Accepted Rate	TOTAL AMOUNT	TOTAL AMOUNT in words		
1	Appendix I-LSGD Road Restoration Charges for 20mm Open graded Chipping Carpet(Mullassery Panchayath)							
1.001	3.5.3 - Excavation in Soil using Hydraulic Excavator and Tippers with disposal upto 1000 m Excavation for roadwork in soil with hydraulic excavator of 0.9 cum bucket capacity including cutting and loading in tippers, trimming bottom and side slopes, in accordance with requirements of lines, grades and cross-sections, and transporting to the embankment location with a lift upto 1.5 m and lead upto 1000 m as per Technical Specification Clause 302.3	2000.000		36.00	72000.00	Rupees Seventy Two Thousand Zero Zero Only		
1.002	4.1.A.1 - Granular Sub-base with Well Graded Material (Table 400.1) (A) By Mix in Place Method Construction of granular sub-base by providing well graded material, spreading in uniform layers with motor grader on prepared surface, mixing by mix in place method with rotavator at OMC, and compacting with smooth wheel roller to achieve the desired density, complete as per Technical Specification Clause 401. (i) For Grading I Material	1000.000	cum	2664.00	2664000.00	Rupees Twenty Six Lakh Sixty Four Thousand Zero Zero Only		
1.003	4.9 - Wet Mix Macadam Providing, laying, spreading and compacting graded stone aggregate to wet mix macadam specification including premixing the material with water at OMC	1000.000	cum	2967.00	2967000.00	Rupees Twenty Nine Lakh Sixty Seven Thousand Zero Zero Only		

Sl No	Description of work	No. or Qty.	Unit	Accepted Rate	TOTAL AMOUNT	TOTAL AMOUNT in words
	in mechanical mixer (Pug Mill), carriage of mixed material by tipper to site, laying in uniform layers in sub-base/base course on a well prepared sub-base and compacting with smooth wheel roller of 80 to 100kN weight to achieve the desired density including lighting, barricading and maintenance of diversion, etc as per Tables 400.11 & 400.12 and Technical Specification Clause 406. By Mechanical Means with 1 km lead					
1.004	5.1.1a - Prime Coat :- Low porosity Providing and applying primer coat with bitumen emulsion (SS-1) on prepared surface of granular base including cleaning of road surface and spraying primer at the rate of 0.70-1.0 kg/sqm using mechanical means as per Technical Specification Clause 502	Į.	sqm	78.00	390000.00	Rupees Three Lakh Ninety Zero Thousand Zero Zero Only
1.005	5.2.3a - Tack Coat Providing and applying tack coat with Bitumen emulsion (RS-1) using emulsion distributor at the rate of 0.25 to 0.30 kg per sqm on the prepared granular surfaces treated with primer & cleaned with Hydraulic broom as per Technical Specification Clause 503.	e-PL/ OF PL	sqm	17.00 FOR THE MANA PAKS	85000.00	Rupees Eighty Five Thousand Zero Zero Only
1.006	5.9.1.2a - 20mm thick Open-Graded Premix Carpet using Bituminous (penetration grade/modified bitumen) Binder - Bitumen S-65 Providing, laying and rolling of open-graded premix carpet of 20 mm thickness composed of 13.2 mm to 5.6 mm aggregates either using penetration grade bitumen or emulsion to required line, grade and level to serve as wearing course on a previously prepared base, including mixing in a suitable plant, laying and rolling with a three wheel 80-100 kN static roller capacity, finished to required level and grades to be followed by seal coat of either Type A or Type B or Type C as per Technical		sqm	198.00	990000.00	Rupees Nine Lakh Ninety Zero Thousand Zero Zero Only

Sl No	Description of work	No. or Qty.	Unit	Accepted Rate	TOTAL AMOUNT	TOTAL AMOUNT in words
	Specification Clause 508. Case - I By Manual Means (II) Bitumen (S-65)					
1.007	5.12.A.3.2a - Seal Coat - Manual Means - Type C - Bitumen S-65 Providing and laying seal coat sealing the voids in a bituminous surface laid to the specified levels, grade and cross fall using Type A, Type B and Type C as per Technical Specification Clause 510 A. By Manual Means :- Case - III : Type C (II) Bitumen (S-65)	5000.000	sqm	85.00	425000.00	Rupees Four Lakh Twenty Five Thousand Zero Zero Only
2	Appendix II-LSGD Road Res Panchayath)	storation Cha	arges for	20mm Open grad	ded Chipping Ca	rpet(Pavaratty
2.001	3.5.3 - Excavation in Soil using Hydraulic Excavator and Tippers with disposal upto 1000 m Excavation for roadwork in soil with hydraulic excavator of 0.9 cum bucket capacity including cutting and loading in tippers, trimming bottom and side slopes, in accordance with requirements of lines, grades and cross-sections, and transporting to the embankment location with a lift upto 1.5 m and lead upto 1000 m as per Technical Specification Clause 302.3	2000.000	cum MTFORMUBLIC W	ORKS	SEMENT	Rupees Seventy Two Thousand Zero Zero Only
2.002	4.1.A.1 - Granular Sub-base with Well Graded Material (Table 400.1) (A) By Mix in Place Method Construction of granular sub-base by providing well graded material, spreading in uniform layers with motor grader on prepared surface, mixing by mix in place method with rotavator at OMC, and compacting with smooth wheel roller to achieve the desired density, complete as per Technical Specification Clause 401. (i) For Grading I Material	1000.000	cum	2663.00	2663000.00	Rupees Twenty Six Lakh Sixty Three Thousand Zero Zero Only
2.003	4.9 - Wet Mix Macadam Providing, laying, spreading and compacting graded stone aggregate to wet mix macadam specification including premixing the material with water at OMC in mechanical mixer (Pug	1000.000	cum	2967.00	2967000.00	Rupees Twenty Nine Lakh Sixty Seven Thousand Zero Zero Only

Sl No	Description of work	No. or Qty.	Unit	Accepted Rate	TOTAL AMOUNT	TOTAL AMOUNT in words
	Mill), carriage of mixed material by tipper to site, laying in uniform layers in sub-base/base course on a well prepared sub-base and compacting with smooth wheel roller of 80 to 100kN weight to achieve the desired density including lighting, barricading and maintenance of diversion, etc as per Tables 400.11 & 400.12 and Technical Specification Clause 406. By Mechanical Means with 1 km lead					
2.004	5.1.1a - Prime Coat :- Low porosity Providing and applying primer coat with bitumen emulsion (SS-1) on prepared surface of granular base including cleaning of road surface and spraying primer at the rate of 0.70-1.0 kg/sqm using mechanical means as per Technical Specification Clause 502	4	sqm	80.00	400000.00	Rupees Four Lakh Zero Zero Zero Only
2.005	5.2.3a - Tack Coat Providing and applying tack coat with Bitumen emulsion (RS-1) using emulsion distributor at the rate of 0.25 to 0.30 kg per sqm on the prepared granular surfaces treated with primer & cleaned with Hydraulic broom as per Technical Specification Clause 503.	e-PL/ OF PI	sqm			Rupees Eighty Five Thousand Zero Zero Only
2.006	5.9.1.2a - 20mm thick Open-Graded Premix Carpet using Bituminous (penetration grade/modified bitumen) Binder - Bitumen S-65 Providing, laying and rolling of open-graded premix carpet of 20 mm thickness composed of 13.2 mm to 5.6 mm aggregates either using penetration grade bitumen or emulsion to required line, grade and level to serve as wearing course on a previously prepared base, including mixing in a suitable plant, laying and rolling with a three wheel 80-100 kN static roller capacity, finished to required level and grades to be followed by seal coat of either Type A or Type B or Type C as per Technical Specification Clause 508.		sqm	198.00	990000.00	Rupees Nine Lakh Ninety Zero Thousand Zero Zero Only

Sl No	Description of work	No. or Qty.	Unit	Accepted Rate	TOTAL AMOUNT	TOTAL AMOUNT in words
	Case - I By Manual Means (II) Bitumen (S-65)					
2.007	5.12.A.3.2a - Seal Coat - Manual Means - Type C - Bitumen S-65 Providing and laying seal coat sealing the voids in a bituminous surface laid to the specified levels, grade and cross fall using Type A, Type B and Type C as per Technical Specification Clause 510 A. By Manual Means: - Case - III: Type C (II) Bitumen (S-65)		sqm	87.00	435000.00	Rupees Four Lakh Thirty Five Thousand Zero Zero Only

The above work awarded to the contractor CIJOE.P.S,ATNPC0519J, at his quoted rate for individual items at a total accepted PAC 15205000(One Crore Fifty Two Lakh Five Thousand Only) as per the condition of the contract.

